

SPECIFICATIONS

General Specifications

| Item | Specification |
|--|---------------|
| MERCON® Multi-Purpose Automatic Transmission Fluid XT-2-QDX (US); XT-2-LM12 (Canada) | MERCON® |
| Threadlock and Sealer TA-25 | WSK-M2G351-A5 |

Torque Specifications

| Description | Nm | lb-ft | lb-in |
|--|----|-------|-------|
| Clevis-to-hydraulic lift cylinder rod bolts | 20 | 15 | — |
| Compression panel screws | 2 | — | 18 |
| Convertible top ajar switch screw | 9 | — | 80 |
| Convertible top frame number 5 bow pivot bolts | 9 | — | 80 |

Torque Specifications (Continued)

| Description | Nm | lb-ft | lb-in |
|--|----|-------|-------|
| Convertible top latch screws | 6 | — | 53 |
| Convertible top pump and motor assembly nuts | 4 | — | 35 |
| Header form panel screws | 5 | — | 44 |
| Hydraulic lift cylinder bracket bolts | 20 | 15 | — |
| Hydraulic line-to-lift cylinder fittings | 4 | — | 35 |
| Hydraulic line-to-motor fittings | 4 | — | 35 |
| L-bracket bolts | 27 | 20 | — |
| Pivot bracket-to-quarter panel bracket bolts | 11 | 8 | — |
| Pivot bracket bolts | 48 | 35 | — |
| Weatherstrip retaining channel screws | 6 | — | 53 |